

CATIONOL ADD



阳离子表面加脂剂

成分

Cationol ADD 是阳离子加脂剂, 适合在顶加脂浴使用.

Cationol ADD 由植物油衍生物组成.

Cationol ADD 非常适合在表染浴使用, 颜色非常鲜艳, 可节省染料成本.

Cationol ADD 赋予表面手感光滑及舒适.

Cationol ADD 适合水染革, 不影响涂饰工段.

Cationol ADD 耐光性及稳定性优良.

为了达到最好的效果, **Cationol ADD** 要预先与 18-22°C 的冷水之中稀释 1:10.

应用范围

A. 不适合铬复鞣浴.

B. 对阴离子化工非常敏感. **Cationol ADD** 会与阴离子化工如金属, 复鞣剂, 加脂剂等反应及沉淀.

C. 顶加脂浴: 大量水. 1.0-2.0% **Cationol ADD** 15'.

D. 表染浴: 染料吸收完全后. 大量水. 1.0-2.0% **Cationol ADD** 15'.

特性

外观:	白色液体
分析:	pH 3.0-4.0
有效成分:	30-32%
电性:	阳离子
稳定性:	单项加脂. 对阴离子化工在铬复鞣浴, 中和浴, 复鞣浴, 主加脂浴非常敏感. 对铬及铝不稳定.
储存方法:	室温. 如出现霜冻, 搅拌均匀即可. 存放在阴凉及通风的库房.
保质期:	密封容器约 18 月.

包装

120KGS 塑料桶

The information and technical advice are provided to you 'as is' and the Company expressly disclaims all warranties of any kind, either implied or expressed. You agree to indemnify and hold harmless the Company and its representatives, subsidiaries, affiliates, related parties, officers, directors, employees, agents from any claim or demand, including reasonable legal fees, that may be filed by any third party, arising out of your conduct or connection with the use of "Product Literature" or "Technical Information" or "Technical Advice" or "Technical Guidance" or any "Recommendation".