

丝卡隆 1102



硅油加脂剂

成份

丝卡隆 1102 是硅油综合加脂剂，使皮粒面与内部的柔软性很平均。

丝卡隆 1102 适合大量填充，复鞣的自然摔箱包革，使皮具有柔软及重量轻的手感。

丝卡隆 1102 与 依丽卡隆 6SKT 一起加工会去掉批内部的骨头手感，并不用酸性软化酶或复灰过程。

丝卡隆 1102 的原料具有优良耐光牢度，即使长时间储存也不会产生任何异味，使皮具有重量轻，柔软与毛茸茸手感。

由于丝卡隆 1102 是一种综合加脂剂，长期保存可能会分层现象。

为了达到最好的效果 丝卡隆 1102 要预先加热到 25-35C，再把它乳化到 40-50C 的水之中。

应用范围

A. 鞋面革：6-8% 丝卡隆 1102.

B. 箱包革：10-12% 丝卡隆 1102.

C. 植鞣革：10-12% 丝卡隆 1102.

特性

外观:	黄色液体
分析:	pH 5.0-6.5
有效成份:	53-56%
电性:	阴离子
稳定性:	用于复鞣，中和，加脂浴。对铬，铝敏感。
储存方法:	室温。如出现霜冻，搅拌均匀即可。 存放在阴凉及通风的库房。
保质期:	密封容器约 12 月。

包装

120KGS 塑料桶

The information and technical advice are provided to you 'as is' and the Company expressly disclaims all warranties of any kind, either implied or expressed. You agree to indemnify and hold harmless the Company and its representatives, subsidiaries, affiliates, related parties, officers, directors, employees, agents from any claim or demand, including reasonable legal fees, that may be filed by any third party, arising out of your conduct or connection with the use of "Product Literature" or "Technical Information" or "Technical Advice" or "Technical Guidance" or any "Recommendation".